

ELULED




ELULED Emergency Luminaires LED Emergency Twinspot

Specifications

Application	Anti-Panic Lighting, Escape Route lighting, Hazardous Area Lighting
Mounting	Direct mounting to wall & ceiling
Version	Manual Test, Self Test, DALI
Mode	Non-maintained
Emergency Duration	1/3/8 hours
Light Source	2x25 mid power led spot, 4000-6500K, CRI>80
Battery	3.6, 4.8, 7.2 Volt High temperature battery block, Ni-Cd, Ni-MH, 12V 7Ah VRLA
Wiring	Up to 2x2,5 mm ² quick fit terminal block
Power Supply	230 Volt, 50/60Hz
Protection	IP65
Temperature Range	0-45°C, VRLA 0-25°C
Electrical Class	Class II (no earth wiring required)
Material	Thermoplastic housing

Dimensions (mm)



Ordering Details

Code	Type	Duration	Light Output	Battery	
ELULED-345-1H	ECO	1 hour	2 x 515 Lumen	3.6V, 4.5Ah Ni-Cd	
ELULED-445-1H			2 x 685 Lumen	4.8V, 4.5Ah Ni-Cd	
ELULED-645-1H			2 x 765 Lumen	7.2V, 4.5Ah Ni-Cd	
ELULED-345-3H		3 hours	2 x 220 Lumen	3.6V, 4.5Ah Ni-Cd	
ELULED-445-3H			2 x 300 Lumen	4.8V, 4.5Ah Ni-Cd	
ELULED-645-3H			2 x 430 Lumen	7.2V, 4.5Ah Ni-Cd	
ELULED-1207-3H		8 hours	2 x 750 Lumen	12V, 7Ah VRLA	
ELULED-645-8H			2 x 175 Lumen	7.2V, 4.5Ah Ni-Cd	
ELULED-1207-8H			2 x 280 Lumen	12V, 7Ah VRLA	
ELULED-340-1H-ST	SELF TEST	1 hour	2 x 450 Lumen	3.6V, 4.0Ah Ni-MH	
ELULED-345-1H-ST			2 x 515 Lumen	3.6V, 4.5Ah Ni-Cd	
ELULED-440-1H-ST			2 x 610 Lumen	4.8V, 4.0Ah Ni-MH	
ELULED-445-1H-ST		2 x 685 Lumen	4.8V, 4.5Ah Ni-Cd		
ELULED-645-1H-ST		2 x 765 Lumen	7.2V, 4.5Ah Ni-Cd		
ELULED-340-3H-ST		3 hours	2 x 200 Lumen	3.6V, 4.0Ah Ni-MH	
ELULED-345-3H-ST			2 x 220 Lumen	3.6V, 4.5Ah Ni-Cd	
ELULED-440-3H-ST			2 x 255 Lumen	4.8V, 4.0Ah Ni-MH	
ELULED-445-3H-ST		2 x 300 Lumen	4.8V, 4.5Ah Ni-Cd		
ELULED-640-3H-ST		2 x 390 Lumen	7.2V, 4.0Ah Ni-MH		
ELULED-645-3H-ST		2 x 430 Lumen	7.2V, 4.5Ah Ni-Cd		
ELULED-1207-3H-ST		DALI	3 hours	2 x 750 Lumen	12V, 7Ah VRLA
ELULED-340-3H-DALI				2 x 200 Lumen	3.6V, 4.0Ah Ni-MH
ELULED-345-3H-DALI				2 x 220 Lumen	3.6V, 4.5Ah Ni-Cd
ELULED-440-3H-DALI				2 x 255 Lumen	4.8V, 4.0Ah Ni-MH
ELULED-445-3H-DALI	2 x 300 Lumen			4.8V, 4.5Ah Ni-Cd	
ELULED-640-3H-DALI	2 x 390 Lumen			7.2V, 4.0Ah Ni-MH	
ELULED-645-3H-DALI	2 x 430 Lumen	7.2V, 4.5Ah Ni-Cd			
ELULED-1207-3H-DALI			2 x 750 Lumen	12V, 7Ah VRLA	

Polar Lighting Distribution Curve

